

CONDUIT BUSHING

Insulated - With Lug - Malleable Iron

Malleable Iron insulated conduit bushings with lug are used with locknuts to connect threaded Rigid/IMC conduits to box or enclosure. Rated 105°C plastic liner provides a smooth rounded surface at the entrance to prevent damage to wire insulation.

Material:

Body: Malleable iron

Throat Insulator: Plastic

Lug: Aluminum

Surface Finish:

Zinc plated

Lug Installation Screw Holes:

Two

Certification & Standard

Manufactured to Underwriters Laboratory


Safety Standards UL 514B

UL File No.: E547877



Dimensions:

The dimensions of malleable iron conduit bushing with lug are as indicated in Table 1.



Tabel 1 - Dimensions of malleable iron conduit bushing with lug

Catalog Number	Trade Size	Lug Wire Size		Dim A	Dim B	Dim C
	in.	Min.	Max.	in.	in.	in.
IHGB050	1/2"	14	4	1.040	0.558	0.433
IHGB075	3/4"	14	4	1.260	0.748	0.492
IHGB100	1"	14	4	1.555	0.965	0.551
IHGB125	1-1/4"	14	4	1.953	1.300	0.602
IHGB150	1-1/2"	14	4	2.170	1.480	0.650
IHGB200	2"	14	4	2.670	1.810	0.677
IHGB250	2-1/2"	14	1/0	3.160	2.295	0.787
IHGB300	3"	14	1/0	3.850	2.827	0.866
IHGB350	3-1/2"	14	1/0	4.276	3.346	0.866
IHGB400	4"	14	1/0	4.870	3.780	0.906
IHGB500	5"	14	1/0	6.200	4.822	1.063
IHGB600	6"	14	1/0	7.244	5.708	1.142